Docket No. 0717-0459P

Art Unit: 2623 Page 2 of 8

AMENDMENTS TO THE CLAIMS

1. (Original) An image synthesis apparatus, comprising:

a right infrared camera and a left infrared camera;

a right visible light camera and a left visible light camera; and

a first image synthesis processing device for synthesizing data output from the

right infrared camera and the left infrared camera and data output from the right visible

light camera and the left visible light camera so that a three-dimensional thermal image

and a three-dimensional visible light image are observed by an observer as overlapping

each other.

2. (Original) An image synthesis apparatus according to claim 1, wherein the

first image synthesis processing device includes:

a synchronous signal generator for generating a synchronous signal;

a second image synthesis processing device for synthesizing at least a portion of

right infrared image data output from the right infrared camera and at least a portion of

right visible light image data output from the right visible light camera in response to a

synchronous signal generated by the synchronous signal generator so as to generate

right synthesis image data;

a third image synthesis processing device for synthesizing at least a portion of

left infrared image data output from the left infrared camera and at least a portion of left

visible light image data output from the left visible light camera in response to a

Docket No. 0717-0459P

Art Unit: 2623

Page 3 of 8

synchronous signal generated by the synchronous signal generator so as to generate

left synthesis image data; and

a data output device for outputting the right synthesis image data and the left

synthesis image data in a prescribed order in response to a synchronous signal

generated by the synchronous signal generator.

3. (Original) An image synthesis apparatus according to claim 2, wherein:

the second image synthesis processing device synthesizes a portion of the right

infrared image and the entire right visible light image data, and

the third image synthesis processing device synthesizes a portion of the left

infrared image data and the entire left visible light image data.

4. (Original) An image synthesis apparatus according to claim 2, further

comprising a monitor for displaying a right synthesis image and a left synthesis image in

a prescribed order based on the right synthesis image data and the left synthesis image

data which are output from the data output device.

5. (Original) An image synthesis apparatus according to claim 4, further

comprising a polarizer for polarizing the right synthesis image in a first direction and

polarizing the left synthesis image in a second direction different from the first direction,

in response to a synchronous signal generated by the synchronous signal generator.

Docket No. 0717-0459P Art Unit: 2623

Page 4 of 8

6. (Original) An image synthesis apparatus according to claim 1, wherein the first image synthesis processing device includes:

a synchronous signal generator for generating a synchronous signal; and a data output device for outputting right infrared image data output from the right infrared camera, right visible light image data output from the right visible light camera, left infrared image data output from the left infrared camera, and left visible light image data output from the left visible light camera in a prescribed order, in response to a synchronous signal generated by the synchronous signal generator.

7. (Original) An image synthesis apparatus according to claim 1, wherein the first image synthesis processing device includes:

a second image synthesis processing device for synthesizing right infrared image data output from the right infrared camera and left infrared image data output from the left infrared camera so as to generate three-dimensional thermal image data;

a third image synthesis processing device for synthesizing right visible light image data output from the right visible light camera and left visible light image data output from the left visible light camera so as to generate three-dimensional visible light image data; and

a fourth image synthesis processing device for synthesizing the threedimensional thermal image data and the three-dimensional visible light image data so as to generate three-dimensional overall image data.

Docket No. 0717-0459P

Art Unit: 2623 Page 5 of 8

8. (Original) An image synthesis apparatus according to claim 7, wherein the

three-dimensional thermal image data includes a plurality of temperature levels, and a

plurality of color tones are respectively assigned to the plurality of temperature levels.

9. (Original) An image synthesis apparatus according to claim 7, wherein the

three-dimensional overall image data includes three-dimensional coordinate data, and

the three-dimensional overall image data is converted into two-dimensional data by

transforming the three-dimensional coordinate data into two-dimensional coordinate

data projected onto a prescribed plane in a three-dimensional coordinate space.

10. (Currently Amended) An image synthesis apparatus, comprising:

a slit device including a plurality of slits;

an infrared directing device for directing infrared toward a subject through the slit

device;

a plurality of infrared cameras provided in a direction substantially perpendicular

to a direction in which the infrared is directed toward the subject; and

a plurality of visible light cameras provided in a direction substantially perpendicular

to a direction in which the visible light images a subject; and

an image synthesis processing device for synthesizing a plurality of thermal

image data output from the plurality of infrared cameras so as to generate three-

dimensional thermal image data, and

U.S. Application No. 09/788,497 Docket No. 0717-0459P

No. 0717-0459P Art Unit: 2623

Page 6 of 8

said image synthesis processing device synthesizing a plurality of visible light

image data from the plurality of visible light cameras so as to generate three-dimensional

visible light image data.

11. (Original) An image synthesis apparatus according to claim 10, wherein the

image synthesis processing device generates the three-dimensional thermal image data

based on a difference in shape between heat ray patterns reflected by the subject and

respectively imaged by the plurality of infrared cameras.